

## Battery-Operated Hydraulic Crimping / Cutting / Bending Tool

# TRILINER C

### Technical Data

<b>Crimping / Cutting Force</b>	70 kN
<b>Opening Width</b>	30 mm (Cu/Al) 20 mm (Al/St)
<b>Battery Voltage</b>	18 V
<b>Weight*</b>	2.1 kg
<b>Dimensions* L x W x H</b>	375 x 75 x 95 mm
<b>Stroke</b>	21 mm

\* without battery and attachment

MasterBase technology offers the following battery options, select your tool here:

Item No.	Item	Suitable for batteries from
78002100	TriLiner C Ma	Makita 18 V
78102100	TriLiner C-Set Ma**	Makita 18 V
76002600	TriLiner C Bo	Bosch 18 V



**Crimping, cutting and bending:** This tool cuts Cu cable and ACSR; crimps cable lugs or connectors with narrow C-shaped crimping dies (CS) up to 240 mm<sup>2</sup> to DIN or bends cable up to 1,000 mm<sup>2</sup>. The pull-pin head ensures quick and easy installation. The tool is therefore ideal for electrical installation with changing areas of application - with a bending attachment especially for installation work in shafts or electrical installations in angled areas.

### Top Features Comfort Serie "TriLiner C"

- » Equipped with MasterBase technology for flexible selection of the Makita or Bosch battery
- » Interchangeable head allows three applications
- » Design ideally for working in narrow areas
- » Automatic return simplifies the work process
- » Fatigue-free working through ergonomic, lightweight construction
- » LED working field illumination

**\*\*Scope of Delivery Set:** TriLiner C Ma, Makita battery 18 V/5 Ah BL1850B (Item No. 793000115), Makita battery charger DC18RC (Item No. 79300120), transportation case  
**The tool attachments are not included.**

### Attachments

**Crimping Head SL-6CJ**

Crimping Die Series CS (narrow C-shaped)  
**Item No. 78002010**

**Cutting Head Cable SL-CH**

**Item No. 78002020**




**Cutting Head Cable SL-ACSR**

**Item No. 78002030**

**Cable Bender SLCB-JAW**

**Item No. 78002040**

## Crimping Head

SL-6CJ		Cable
Cu/Al to DIN 48083		Cu: 6 – 240 mm <sup>2</sup> Al: 10 – 240 mm <sup>2</sup>
ACSR		Al: 16 – 185 mm <sup>2</sup> St: 2.5 – 25 mm <sup>2</sup>
Tubular Cable Connector (similar to DIN)		10 – 240 mm <sup>2</sup>



A sample processing is recommended. Inquiry to P +49 40 511 28-0.

## Cutting Head Cu/Al

SL-CH	
Opening Width	Max. Ø 30 mm
Application	Cu/Al Strand Cu/Al Energy Cable
Item No.	78002020



## Cutting Head ACSR

SL-ACSR	
Opening Width	Max. Ø 20 mm
Application	ACSR single steel core
Item No.	78002030







## Cable Bender

SLCB-JAW	
Cable max.	Ø 1,000 mm <sup>2</sup> (Ø 30 mm)
Item No.	78002040



## Accessories

Item	Type	Description	Item No.	
Transportation Case	KOFF-Km Tri C	Light-weight plastic case with a compartment for two batteries, battery charger	79500138	
Carrying Strap	TR-REC	Carrying strap for battery tools, strap 25 mm wide, 1 snap hook	07542106	
	TR-25-2	Carrying strap for battery tools, strap 25 mm wide, 2 snap hooks	07755001	
	TR-40-2	Carrying strap for battery tools, strap 40 mm wide, 2 snap hooks	07755002	

Do you have a Comfort Series tool with an unsuitable battery holder?  
Talk to us, with Retrofit we can make it fit your requirements.