

Battery-Operated Hydraulic Crimping Tool

PRESSMAX-C6-C

Technical Data

| | |
|------------------------------|-------------------|
| Crimping Force | 60 kN |
| Stroke | 18 mm |
| Battery Voltage | 18 V |
| Weight* | 3.4 kg |
| Dimensions* L x W x H | 340 x 82 x 277 mm |
| Head | 180° rotatable |

* without battery

MasterBase technology offers the following battery options, select your tool here:

| Item No. | Item | Suitable for batteries from |
|----------|------------------------|-----------------------------|
| 76746500 | PressMax-C6-C Ma | Makita 18 V |
| 76846500 | PressMax-C6-C-Set Ma** | Makita 18 V |
| 76762300 | PressMax-C6-C Bo | Bosch 18 V |
| 76766500 | PressMax-C6-C Hi | Hilti 22 V (B22) |



This tool enables crimping cable lugs or connectors with narrow C-shaped crimping dies (CS) up to 300 mm² to DIN. This powerful crimping tool is ideal for applications in switch cabinet construction, electrical assembly and for energy suppliers

Top Features Comfort Serie "PressMax-C6-C"

- » Equipped with MasterBase technology for flexible selection of the Makita, Bosch or Hilti battery
- » Suitable for narrow C-shaped crimping dies (CS), DIN to 300 mm²
- » Design ideally for working in narrow areas
- » Selectable automatic return simplifies the work process
- » Fatigue-free working through ergonomic, lightweight construction
- » LED working field illumination







Crimping Ranges

| Application | | Cable |
|--|--|--|
| Cu/Al to DIN 48083 | | Cu: 6 – 300 mm ² Al: 10 – 300 mm ² |
| ACSR | | Al: 16 – 120 mm ² St: 2.5 – 25 mm ² |
| Pre-Rounding | | SE: 35 – 300 mm ² SM: 10 – 240 mm ² |
| Tubular Cable Connectors (similar to DIN) | | 10 – 300 mm ² |
| Arbor Crimping | | 10 – 95 mm ² |
| Trapezoid Crimping | | 10 – 240 mm ² |
| WM Crimping | | 10 – 300 mm ² |
| H Clamps | | 70 mm ² |

****Scope of Delivery Set:** PressMax-C6-C Ma, Makita battery 18 V/5 Ah BL1850B (Item No. 79300115), Makita battery charger DC18RC (Item No. 793000120), carrying strap, transportation case

A sample processing is recommended. Inquiry to P +49 40 511 28-0.
 Do you have a Comfort Series tool with an unsuitable battery holder?
 Talk to us, with Retrofit we can make it fit your requirements.

Accessories

| Item | Type | Description | Item No. | |
|---|------------------|---|----------|---|
| Transportation Case PressMax-C6-C Ma PressMax-C6-C Bo | KOFF-Km PM-C5-14 | Light-weight plastic case with a compartment for two batteries, battery charger | 79500127 |  |
| Carrying Strap | TR-REC | Carrying strap for battery tools, strap 25 mm wide, 1 snap hook | 07542106 |  |
| | TR-25-2 | Carrying strap for battery tools, strap 25 mm wide, 2 snap hooks | 07755001 |  |
| | TR-40-2 | Carrying strap for battery tools, strap 40 mm wide, 2 snap hooks | 07755002 |  |