

SCHLEIFSCHEIBEN SANDING DISCS

Korund Klett / Aluminium Oxide, Velcro

Abmessungen <i>Dimensions</i>	Typ <i>Type</i>	Korn <i>Grain</i>	Artikel-Nr. <i>Item No.</i>	Min. Abnahmemenge <i>Min. Quantity Order</i>
Ø 50 mm	KOK50-K	40	19000104	100 Stk. 100 pcs.
		60	19000106	
		80	19000108	
		100	19000110	
		120	19000112	
		150	19000115	
		180	19000118	
		220	19000122	
		240	19000124	
		320	19000132	
Ø 75 mm	KOK75-K	40	19000204	100 Stk. 100 pcs.
		60	19000206	
		80	19000208	
		100	19000210	
		120	19000212	
		150	19000215	
		180	19000218	
		220	19000222	
		240	19000224	
		320	19000232	
Ø 115 mm	KOK115-K	24	19000502	100 Stk. 100 pcs.
		40	19000504	
		60	19000506	
		80	19000508	
		100	19000510	
		120	19000512	
		150	19000515	
		180	19000518	
		220	19000522	
		240	19000524	
Ø 125 mm	KOK125-K	24	19000602	100 Stk. 100 pcs.
		40	19000604	
		60	19000606	
		80	19000608	
		100	19000610	
		120	19000612	
		150	19000615	
		180	19000618	
		220	19000622	
		240	19000624	
Ø 150 mm	KOK150-K	40	19000704	100 Stk. 100 pcs.
		60	19000706	
		80	19000708	
		100	19000710	
		120	19000712	
		150	19000715	
		180	19000718	
		220	19000722	
		240	19000724	
		320	19000732	
		400	19000740	



Info

Korn: Korund
Bindung: Kunstharz
Streuart: halboffen
Hauptanwendungen: Holz, Metall Universal
Weitere Anwendungen: Kunststoff, Spachtel, Lack, Farbe, Edelstahl

Grain: Aluminium Oxide
Bonding: Synthetic Resin
Coating: Close
Main Application: Wood, Metals universal
Further Applications: Plastics, Paints, Varnishes, Filler, Stainless Steel

Korund Klett / Aluminium Oxide, Velcro

Abmessungen Dimensions	Typ Type	Korn Grain	Artikel-Nr. Item No.	Min. Abnahmemenge Min. Quantity Order
Ø 125 mm 8-Loch/Hole Lochkreis/Bolt Circle Ø 65 mm	KOK125-K-ABS	40	17199554	100 Stk. 100 pcs.
		60	17199556	
		80	17199558	
		100	17199560	
		120	17199562	
		150	17199565	
		180	17199568	
		220	17199572	
		240	17199574	
		320	17199582	
		400	17199590	
Ø 150 mm 6-Loch/Hole Lochkreis/Bolt Circle Ø 80 mm	KOK150-K-ABS	40	17199554	100 Stk. 100 pcs.
		60	17199556	
		80	17199558	
		100	17199560	
		120	17199562	
		150	17199565	
		180	17199568	
		220	17199572	
		240	17199574	
		320	17199582	
		400	17199590	



Info

Korn: Zirkonkorund
Bindung: Kunstharz
Streuart: halboffen
Hauptanwendungen:
 Holz, Metall Universal
Weitere Anwendungen:
 Edelstahl, Farbe, Lack,
 Spachtel, Kunststoff

Grain: Aluminium Oxide
Bonding: Synthetic Resin
Coating: Half-open
Main Application:
 Wood, Metals universal
Further Applications:
 Stainless Steel, Paints,
 Varnishes, Fillers, Plastics