

CH-24

MEISSELHAMMER CHISEL HAMMER

Druckluft-Meißelhammer für Entrostungs- und Reinigungsarbeiten, zum Entfernen von Schweißpunkten und Entgraten; im Maschinenbau, auf Werften, in Gießereien sowie in der Betonsanierung.

Pneumatic chisel hammer for rust removal and cleaning jobs, removing welding spots and deburring; in machine building industry, ship yards, foundries as well as for concrete repair and refurbishment.



VORTEILE

- Schnelles Wechseln des Zubehörs durch Schnellwechsellahme.
- Vierkantaufnahme mit Verdrehsicherung.
- Leichter, kleiner und besonders wartungsarmer Aufbau mit hoher Standzeit.
- Stabform ideal für Arbeiten bei engen Platzverhältnissen.
- Niedrige Vibrationswerte für ermüdungsfreies Arbeiten.

BENEFITS

- Quick-changing chuck for easy and quick accessory change.
- Square shaft with twist lock.
- Light-weight, compact and low-maintenance design and long service life.
- Elongated body design is ideal for working in confined spaces.
- Fatigue-free working thanks to low vibration values.

TECHNISCHE DATEN TECHNICAL DATA

Artikel	Item	CH-24
Schläge	Blows	4.000 min ⁻¹
Aufnahme	Chuck	Vierkant / Square 12,7 mm
Länge	Length	184 mm
Gewicht	Weight	1,6 kg
Luftverbrauch	Air Consumption	3,4 l/s
Luftanschluss	Air Connection	G 3/8"
Empf. Schlauch-Ø	Recomm. Hose Ø	9 mm
Vibration	Vibrations	16,2 m/s ² (± 2,1 m/s ²)
Max. Betriebsdruck	Max. Working Pressure	6,3 bar
Artikel-Nr.	Item No.	81126200

Lieferumfang

Werkzeug mit Schlauchtülle, Adapter PT 3/8 x NPT 3/8 und Meißel TP15166

Scope of Delivery

Tool with hose nipple, adapter PT 3/8 x NPT 3/8 and chisel TP15166

ZUBEHÖR ACCESSORIES

Meißel / Chisel

Aufnahme Chuck	Typ Type	Abmessungen B x L Dimensions W x L	Beschreibung Description	Artikel-Nr. Item No.
Vierkant	TP15234	12,7 x 165 mm	Flachmeißel, gerade / Flat chisel, straight	81126201
Square	TP15233	25 x 155 mm	Flachmeißel, gerade / Flat chisel, straight	81126202
12,7 mm	TP15166	25 x 155 mm	Flachmeißel, gebogen / Flat chisel, curved	81126203